

IMAGE PROCESSING APPARATUS, IMAGE PROCESSING  
METHOD, STORAGE MEDIUM, AND PROGRAM

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to a technique of transferring an image to a computer from a digital camera or another apparatus for storing the image, and printing the image or E-mailing the image.

10 Related Background Art

In recent years, with spread of a digital camera, a large amount of images have easily been photographed, taken and stored in a personal computer (PC), and printed by oneself, or attached to an E-mail and  
15 mailed. This can easily be performed.

With this way of use, a large number of pieces of image management software have been brought on sale, by which the image can be managed with the PC, printed and attached to the E-mail.

20 A representative example of the image management software is shown in FIG. 1. In this manner, when a folder containing an image to be displayed is selected from section 1, and an image file in the folder is displayed in a thumb nail form (image obtained by  
25 reducing in size and displaying the original image) in a section 2, so that a user can easily see a large number of images at once. In this case, when a certain

09848372.050401

thumb nail image is selected and double clicked in a section 3, the image can be enlarged and displayed in a separate window. Moreover, when a certain thumb nail is selected and printing is designated, the printing of the image can be executed. Furthermore, when a certain thumb nail is selected and "E-mailing" is designated, mail software is started and the image file is automatically attached to an E-mail.

FIG. 2 shows an example of a printing designation window.

A plurality of thumb nails are selected and "print..." is selected from a menu or the like. Then, the window of FIG. 2 appears. Here, selected thumb nail images 207 are arranged and displayed. A horizontal number of frames  $\times$  a vertical number of frames of images arranged in a sheet can be designated with frame number designations 201, 202. When the selected images are arranged in more than one sheet, the images can be confirmed by pressing a former page button 204 or a next page button 205. Subsequently, when a print button is pushed, the images are printed according to the layout with a printer.

With the display of the thumb nail form, many images can preferably be seen at a glance, but each image size is small. Therefore, some image management software has a "slide show" function with which a plurality of selected thumb nail images are fully

00448372 050401

5     When this is repeated, the selected images can  
       successively be displayed and seen all over the screen.  
       In this case, the display can be returned to the  
       previous image display by pressing an arrow key "←" or  
       a specific key.

In general, in consideration of a PC screen size, the thumb nail is prepared and displayed in a size of about 80 x 60 dots, or 160 x 120 dots at most. In this size of display, it is very difficult to distinguish the image out of focus, the image with manual vibration, or the like. Moreover, it is also difficult to select a supposedly best photographed photograph from the repeatedly taken photographs of the similar scene or the same object.

The user wants to print, e-mail or otherwise send a favorite photograph to an acquaintance, but as

described above it is difficult to find the photograph from many images in the list display with such thumb nail size. Therefore, the user double-clicks the thumb nails one by one, enlarges and displays each image in a separate window and confirms whether the image is good or bad, or reproduces the images with the aforementioned slide show function to successively check the images. In this case, the user performs an operation of memorizing the favorite image, one returning to the thumb nail display screen, and re-selecting only the favorite image from the screen to print the image or attach the image to the E-mail.

As described above, finally the image is to be printed or attached to the E-mail. However, an operation of checking and selecting the image is not correlated with an operation of printing a result or attaching the result to the E-mail, and this is inconvenient in user's operation.

## SUMMARY OF THE INVENTION

An object of the present invention is to solve all or at least one of the aforementioned problems.

Moreover, an object of the present invention is to provide an image processing apparatus, image processing method, storage medium, and program which solves the aforementioned disadvantages, can securely or easily judge whether an image is good or band, and can

selectively process only the good image.

To achieve the objects, according to the present invention there is provided an image processing apparatus comprising:

5           fetching means for fetching in a reduced image from a storage medium in which a stored image and the reduced image corresponding to the stored image are stored;

10           first display control means for displaying the reduced image fetched by the fetching means in a display;

            indication means for indicating the reduced image to be subjected to a specific image processing from the reduced image displayed in the display;

15           second display control means for displaying an image in a size larger than a size of the reduced image indicated by the indication means; and

            execution means for executing the specific image processing on the stored image after the second display control means displays the image in the size larger than the size of the reduced image.

20           Furthermore, in addition to the aforementioned constitution, in the image processing apparatus, the second display control means displays the stored image corresponding to the reduced image indicated by the indication means.

25           Additionally, an object of the present invention

09848372.050401

is to confirm the image by the display of the second display control means without requiring an intricate operation.

5 To achieve the object, in addition to the aforementioned constitution, in the image processing apparatus, an indicator for changing the image to be displayed in the display is displayed.

10 Moreover, in addition to the aforementioned constitution, the image processing apparatus further comprises display changeover means for successively automatically changing the image to be displayed in the display.

15 Furthermore, an object of the present invention is to smoothly shift to a specific image processing with respect to an image judged to be appropriate for the specific image processing.

20 To achieve the object, in addition to the aforementioned constitution, the image processing apparatus further comprises execution instruction means for instructing the specific image processing to be actually performed in the image displayed in the display by the second display control means.

25 In this case, the execution means executes the specific image processing on the image for which the execution is instructed by the execution instruction means.

Further objects and characteristics of the present

09848372-050401

invention will be apparent upon reading the following description of an embodiment with reference to the drawings.

5 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows an example of a display screen of a thumb nail of image management software.

FIG. 2 shows an example of a print window.

FIG. 3 shows an example of a slide show window.

10 FIG. 4 shows an example of a printing designation button, and E-mail designation button.

FIG. 5 shows a management list of selected images.

FIG. 6 shows a procedure for starting a slide show reproduction screen.

15 FIG. 7 shows a processing procedure for a pushed next button.

FIG. 8 shows a processing procedure for a pushed back button.

20 FIG. 9 shows a processing procedure for a pushed printing designation button.

FIG. 10 shows a processing procedure for a pushed E-mail button.

FIG. 11 shows a procedure until a print window is started.

25 FIG. 12 shows a procedure until E-mail software is started.

FIG. 13 shows an example of a digital camera.

09248372.050401  
T04050.22E84860

FIG. 14 shows an example of connection of a computer and camera.

FIG. 15 shows a system constitution example in an embodiment.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS  
(First Embodiment)

FIG. 14 shows a constitution example of a personal computer system as a platform on which the present invention is carried out. In FIG. 14, reference numeral 301 denotes a computer system main body, 302 denotes a display for displaying data, 303 denotes a mouse as a typical pointing device, 304 denotes a mouse button, and 305 denotes a keyboard. A digital camera 310 is connected to the computer system main body via communication cables such as RS-232C and USB.

FIG. 15 is a diagram showing a constitution of an image data management system including software and hardware. In FIG. 15, reference numeral 509 denotes hardware, 505 denotes an operating system (OS) operating on the hardware 509, and 504 denotes application software operating on the OS 505. Additionally, among blocks constituting the hardware 509 and OS 505, a block which is of course included as a constituting factor but is not directly necessary for describing an embodiment of the present invention is not shown. Examples of the not-shown block include

09848372.050401  
FOI050 27E84860



hardware such as CPU and memory, a memory management system as the OS, and the like. In FIG. 15, reference numeral 515 denotes a hard disk for physically storing a file and data. A file system 508 constituting the OS  
5 has a function for allowing the application software to input/output the file without noticing the hardware. A disk IO interface 514 is disposed such that the file system 508 performs reading/writing of the hard disk 515. A drawing management system 507 constituting the  
10 OS has a function for allowing the application software to perform drawing without noticing the hardware. Reference numeral 513 denotes a video interface for allowing the drawing management system 507 to perform the drawing in the display 302. An input device  
15 management system 506 constituting the OS has a function for allowing the application software to receive a user's input without noticing the hardware. Reference numeral 510 denotes a keyboard interface for allowing the input device management system 506 to  
20 receive the input of the keyboard 305, and 512 denotes a mouse interface for allowing the input device management system 506 to receive the input from the mouse 303. The digital camera 301 is connected via RS-232C cable in the present example. The digital camera  
25 is managed by an external interface management system 522 via an RS-232C interface 521. The communication module 305 performs communication with this external

09848372.050401

interface management system. An image management software 501 uses this communication module to exchange image data and information with the camera.

FIG. 13 shows an example of the digital camera. A  
5 USB I/F 1 is connected to PC. A mode dial switch 2 has a play mode 2a, photography mode 2b, stitch assist mode 2c, slide show reproduction mode 2d, and power Off 2e. Reference numeral 3 denotes a compact flash TM (CF) card slot. When only a camera main body is used, the  
10 mode dial switch is turned to another mode from the power Off. On turning on the power, the mode works. In the photography mode, an image preview is displayed in an LCD 4. When a release switch 5 is pushed, the image is photographed and recorded in a CF card 6. In  
15 the play mode, the last photographed and recorded image is displayed in the LCD, and the image is successively fed and reproduced by +- buttons 7a, 7b.

An operation procedure in which the user selects the image, performs slide show reproduction and  
20 subsequently prints the image will next be described.

The user selects a thumb nail for the slide show reproduction in the thumb nail display screen of FIG. 1. In a selecting method, when "select all" is designated from the menu, all thumb nails are brought  
25 to a selected state. In the selected state, a frame color of the thumb nail turns to red, blue or another color. When a plurality of thumb nails are

0904050"22E84860

5

10

15

30

25

can also be returned with an arrow ← key.

Reference numeral 305 denotes a printing designation button. When the user sees the image, and wants to print the image, the user pushes the printing designation button. Then, a designation end mark is displayed on the button as shown by 402 of FIG. 4. This indicates that the user has designated the printing of the image. When the button is pushed once again, the printing designation is canceled, and the display returns to 401. When the user successively displays and checks the image, and finds the image to be printed, the user designates the printing of the image.

When an end button 307 is pushed, the slide show reproduction is ended, the screen 301 disappears, and the original thumb nail display screen shown in FIG. 1 returns. In this case, when the printing of even one image is designated in the slide show screen, a printing window shown in FIG. 2 automatically starts, and the user can enter an operation for continuously printing the images.

An inner processing procedure will be described along a flow of a series of operations.

When the slide show reproduction screen is started, a list of selected images shown in FIG. 5 is transferred from the thumb nail display screen. In this list, an image file path name is stored, and

09848372-050401  
T04050-2ZEB4860

5           In step 601 the list is obtained, and in step 602  
an image file No. 1 of the list is loaded and  
displayed. Subsequently, the buttons 401 and 402 of  
FIG. 4 are displayed in accordance with the value of  
print designation of the list shown in FIG. 5. In this  
10 case, since the initial value is Off, the button 401 is  
displayed. In step 603 the first image being displayed  
is stored in a variable COUNT. Subsequently,  
(COUNT+1)-th image file is loaded. Thereby, the image  
can quickly be displayed for the next image display.

15           When the next button 304 of FIG. 3 is pushed, a  
processing shown in FIG. 7 is performed.

          It is checked in step 702 whether a (COUNT+1)-th  
image to be displayed has already been loaded. When  
the image is not loaded, the image is loaded in step  
20 708. Subsequently in step 703, the image is displayed  
in the screen. Moreover, the button 401 or 402 of FIG.  
4 is displayed in accordance with the printing  
designation value of the list shown in FIG. 5. It is  
checked in step 704 whether the (COUNT+1)-th image is  
25 in a memory. If the image is in the memory, the image  
is deleted in step 705. Next in step 706 a (COUNT+2)-  
th image is loaded, and in step 707 COUNT value is

5           When the back button 303 of FIG. 3 is pushed, a  
processing shown in FIG. 8 is performed.

When the printing designation button is pushed, a processing shown in FIG. 9 is performed.

25           In step 902 a state before the button is pushed is  
obtained from the list of FIG. 5. If in step 903 or  
905 a list holding value is Off, the value is set to

On. If the value is On, the value is set to Off.  
Subsequently in step 904 or 906, the button is again  
displayed in accordance with the setting.

When the user pushes the end button 301 of FIG. 3,  
5 the slide show screen ends, and the thumb nail display  
screen of FIG. 1 returns.

In the thumb nail display screen, a processing  
shown in FIG. 11 is performed.

It is checked in step 1102 whether there is On in  
10 the column of printing designation of the list shown in  
FIG. 5. If there is even one On, the printing window  
of FIG. 2 is started in step 1104. In the printing  
window, the path name of the image file having On in  
the list of FIG. 5 is obtained, the image is loaded,  
15 and the image is used as the displayed image 207 or the  
image whose printing is executed by pushing the print  
button 206.

(Second Embodiment)

In the first embodiment, the example for  
20 performing the printing designation in the slide show  
screen and subsequently automatically starting the  
printing window has been described. In a second  
embodiment, an example for designating an image to be  
attached to the E-mail in the slide show screen and  
25 subsequently automatically starting E-mail software  
will be shown.

The user selects a thumb nail for the slide show

004050"22E84860

reproduction in the thumb nail display screen of FIG.

1. In a selecting method, when "select all" is  
designated from the menu, all thumb nails are brought  
to a selected state. In the selected state, a frame  
5 color of the thumb nail turns to red, blue or another  
color. When a plurality of thumb nails are  
continuously selected from the thumb nail in a certain  
place, the first thumb nail is clicked and brought to  
the selected state. Thereafter, the last thumb nail is  
10 clicked while pushing SHIFT key. Then, the thumb nails  
including intermediate thumb nails are in the selected  
state. Moreover, when a plurality of arbitrary thumb  
nails are selected, CTRL key is pushed, and  
simultaneously the thumb nails are clicked. Then, only  
15 the clicked thumb nails are in the selected state.

After the thumb nail to be subjected to the slide  
show reproduction is selected in this manner, "slide  
show..." is selected from the menu. Then, the slide  
show screen is displayed in the whole screen of the  
20 computer 302 of FIG. 14 as shown in FIG. 3. In this  
case, since the thumb nail display screen of FIG. 1 is  
positioned in the back of the slide show reproduction  
screen. Therefore, the thumb nail display screen  
cannot be displayed or operated.

25 In FIG. 3, reference numeral 301 denotes the whole  
screen, and 302 denotes the displayed image. When the  
back button 303 is pushed, the display can be returned

009848372-050401  
104050-22E84850



to the previous image. When the next button 304 is pushed, the display can advance to the display of the next image. To advance to the next image, instead of this button, the mouse may be clocked, or the space key  
5 or the arrow → key may be pushed in the same manner. Moreover, to return to the previous image, the display can also be returned with the arrow ← key.

Reference numeral 306 denotes an E-mail designation button. When the user sees the image, and  
10 wants to attach the image to the E-mail, the user pushes this button. Then, the designation end mark is displayed on the button as shown by 404 of FIG. 4, and this informs the user of the E-mail designation. When the button is pushed once again, the E-mail designation  
15 is canceled, and the display returns to 403. When the user successively displays and checks the image, and finds the image to be attached to the E-mail, the user designates the attaching of the image.

When the end button 307 is pushed, the slide show  
20 reproduction is ended, the screen 301 disappears, and the original thumb nail display screen shown in FIG. 1 returns. In this case, when the E-mail of even one image is designated in the slide show screen, E-mail software automatically starts, and a new mail with the  
25 image attached thereto is displayed.

The inner processing procedure will be described along the flow of a series of operations.

004050" 22E84860

When the slide show reproduction screen is started, the list of selected images shown in FIG. 5 is transferred from the thumb nail display screen. In this list, the image file path name is stored, and  
5 values for the E-mail designation are all stored with initial value Off designation.

For the slide show reproduction screen, the procedure shown in FIG. 6 is performed.

In step 601 the list is obtained, and in step 602  
10 the image file No. 1 of the list is loaded and displayed. Subsequently, the buttons 403 and 404 of FIG. 4 are displayed in accordance with the value of E-mail designation of the list shown in FIG. 5. In this case, since the initial value is Off, the button 403 is  
15 displayed. In step 603 the first image being displayed is stored in the variable COUNT. Subsequently, (COUNT+1)-th image file is loaded. Thereby, the image can quickly be displayed for the next image display.

When the next button 304 of FIG. 3 is pushed, the  
20 processing shown in FIG. 7 is performed.

It is checked in step 702 whether the (COUNT+1)-th image to be displayed has already been loaded. When the image is not loaded, the image is loaded in step 708. Subsequently in step 703, the image is displayed  
25 in the screen. Moreover, the button 403 or 404 of FIG. 4 is displayed in accordance with the E-mail designation value of the list shown in FIG. 5. It is

0004050" 22E84B60

checked in step 704 whether the (COUNT-1)-th image is  
in the memory. If the image is in the memory, the  
image is deleted in step 705. Next in step 706 the  
(COUNT+2)-th image is loaded, and in step 707 COUNT  
5 value is increased by one. In this case, the previous  
and next images to the image being displayed are loaded  
in the memory. Even when the back or next button is  
pushed, the corresponding image can quickly be  
displayed.

10 When the back button 303 of FIG. 3 is pushed, the  
processing shown in FIG. 8 is performed.

It is checked in step 802 whether the (COUNT-1)-th  
image to be displayed has already been loaded. When  
the image is not loaded, the image is loaded in step  
15 808. Subsequently in step 803, the image is displayed  
in the screen. Moreover, the button 403 or 404 of FIG.  
4 is displayed in accordance with the E-mail  
designation value of the list shown in FIG. 5. It is  
checked in step 804 whether the (COUNT+1)-th image is  
20 in the memory. If the image is in the memory, the  
image is deleted in step 805. Next in step 806 the  
(COUNT-2)-th image is loaded, and in step 807 the COUNT  
value is decreased by one. In this case, the previous  
and next images to the image being displayed are loaded  
25 in the memory. Even when the back or next button is  
pushed, the corresponding image can quickly be  
displayed.

09848372-050401

When the E-mail designation button is pushed, the processing shown in FIG. 10 is performed.

In step 1002 a state before the button is pushed is obtained from the list of FIG. 5. If in step 1003 or 1005 the list holding value is Off, the value is set to On. If the value is On, the value is set to Off. Subsequently in step 1004 or 1006, the button is again displayed in accordance with the setting.

When the user pushes the end button 301 of FIG. 3, the slide show screen ends, and the thumb nail display screen of FIG. 1 returns.

In the thumb nail display screen, the processing shown in FIG. 12 is performed.

It is checked in step 1202 whether there is On in the column of E-mail designation of the list shown in FIG. 5. If there is even one On, in step 1204 the path name of the image file with the E-mail On is obtained. In step 1205 the E-mail software is started and the path name of the image file is passed. In the E-mail software, a new mail screen is displayed, and these image files are attached.

(Third Embodiment)

In the first and second embodiments, in order to reproduce the slide show, the display advances to the next image in response to the user's clear instruction, the end button 301 of FIG. 3 is pushed, and the slide show screen is ended.

As another mode of slide show, the image is displayed for a given time, and subsequently the display is automatically successively changed to that of the next image. In this case, after the last image is display, and the given time elapses, the slide show screen automatically ends.

In this case, while the image is displayed for the given time such as five or ten seconds, the printing designation button or the E-mail designation button is pushed, and thereby the designation can be performed similarly as the first and second embodiment. When the display of the last image ends, the slide show screen automatically ends. When there is the printing designation or the E-mail designation, the printing window or the E-mail software is automatically displayed.

Additionally, the present invention can preferably be applied not only to printing and mail transmission but also to a use mode in which the image is transferred, for example, to the computer from the digital camera. For a storage medium of the digital camera, the number of frames of stored images is limited. Therefore, it is necessary to frequently transfer or delete the image in the storage medium.

The present invention is also preferable in a storage region change processing for transferring the image in this manner.

Moreover, in the aforementioned embodiments, after the printing or another processing is indicated with a reduced image, an original stored image corresponding to the indicated reduced image is displayed as largely  
5 as possible in the screen, but this is not limited. In order to display a content of the reduced image such that the content is more easily recognized, an image larger than the reduced image may be displayed.

Moreover, at least a part or the whole of the  
10 reduced image may be enlarged and displayed.

Additionally, the present invention may be applied to a system constituted of a plurality of apparatuses (e.g., a host computer, interface apparatus, reader, printer, and the like), or to an apparatus constituted  
15 of one unit (e.g., a copying machine, facsimile machine).

Moreover, a program code of software for realizing the aforementioned embodiment function is supplied to an apparatus connected to various devices or a computer  
20 in a system in such a manner that various devices are operated to realize the aforementioned embodiment function. The system or the apparatus computer (CPU or MPU) is operated by operating various devices according to the stored program. The invention carried out in  
25 this manner is also included in a category of the present invention.

Furthermore, in this case, the program code itself

FOI050"22E84860

of the software realizes the function of the  
aforementioned embodiment. The program code itself,  
and means for supplying the program code to the  
computer, for example the storage medium with the  
5 program code stored therein constitute the present  
invention.

Examples of the storage medium with the program  
code stored therein include a floppy disk, hard disk,  
optical disk, magnetic optical disk, CD-ROM, magnetic  
10 tape, nonvolatile memory card, ROM, and the like.

Moreover, when the computer executes the supplied  
program code, the aforementioned embodiment function is  
realized. Additionally, the program code cooperates  
with an operating system (OS) operating in the  
15 computer, another application software, or the like,  
and the aforementioned embodiment function is realized.  
Even in this case, needless to say, the program code is  
included in the embodiment of the present invention.

As described above, when designation means is  
20 disposed in the slide show display, first the user  
displays the image in a large size, can judge whether  
the image is good or band, and can selectively process  
only the good image. Moreover, the image selected in  
this manner is printed or attached to the E-mail  
25 according to the user's final object. This operation  
can continuously be performed without being  
interrupted.

05040372-050401

Moreover, the image processing apparatus of the present invention includes: take-in means for taking in a reduced image from a storage medium in which a stored image and the reduced image corresponding to the stored image are stored; first display control means for displaying the reduced image taken by the take-in means in a display; indication means for indicating the reduced image to be subjected to a specific image processing from the reduced image displayed in the display; second display control means for displaying the reduced image indicated by the indication means in such a manner that the image is more easily recognized; and execution means for executing the specific image processing on the stored image after the second display control means displays the image. Therefore, the image which should not be processed can be prevented from being incorrectly indicated by the reduced image. In a preferable method of displaying the image in a more recognizable manner, the stored image corresponding to the reduced image is displayed, the stored image is displayed in a size larger than that of the reduced image, or at least a part of the reduced image is enlarged and displayed.

Moreover, since the second display control means displays the stored image corresponding to the reduced image indicated by the indication means, the image can be confirmed with a non-reduced stored image.

0504050" 22E34B50



Additionally, since the second display control means displays any one of the images to be displayed in the display, it is unnecessary to simultaneously display another image or to reduce the display screen.

5 The image can be displayed in a large size fully in the display, and can easily be confirmed.

Moreover, since an indicator for changing the image to be displayed in the display is displayed, the displayed large image can successively be changed. All  
10 the images are easily confirmed in the large screen.

Furthermore, since the image processing apparatus further includes display changeover means for successively automatically changing the image to be displayed in the display, an operation of performing a  
15 changeover instruction can be omitted during confirmation of the image.

Additionally, the image processing apparatus further comprises execution instruction means for instructing the specific image processing to be  
20 actually performed in the image displayed in the display by the second display control means, and the execution means executes the specific image processing on the image for which the execution is instructed by the execution instruction means. Therefore, while  
25 seeing the large image, the image processing can actually be performed on the image to be actually processed.

0904050-22E4B60

Moreover, since the printing processing is performed as the specific image processing, the performing of an unnecessary printing is reduced. Particularly, in recent years, by a printer, the image  
5 can be printed with a resolution much higher than a display resolution of the system. Characteristics which cannot easily be recognized during confirmation with the reduced image remarkably appear in the printed image. Therefore, the present invention is effectively  
10 applied during the printing processing.

Moreover, since the image processing apparatus includes edition operation acceptance means for accepting the user's operation, the printing processing smoothly flows and the apparatus is conveniently used.

15 Furthermore, the mail transmission processing is performed as the specific image processing. Therefore, for example, when the image is transmitted via E-mail, a troublesome operation of starting another application to confirm the image during preparation of a new mail  
20 can be omitted, and the apparatus is conveniently used.

Additionally, the apparatus includes mail preparation control means for controlling the apparatus in such a manner that a new mail preparation processing of attaching the image indicated to be  
25 mailed/transmitted is performed during the mail transmission processing. Therefore, the processing can smoothly shift to the processing of preparing the new

0904372-050401

mail.

Moreover, a transfer processing of transferring the stored image to a desired storage region is performed as the specific image processing. Therefore, an operation of starting another application to confirm the image to be transferred and transferring the desired image after confirmation is not required. Therefore, the intricate operation can be omitted and the apparatus is conveniently used.

Moreover, for the storage medium of the digital camera, the number of frames of stored images is limited. Therefore, an operation of transferring the image to the computer is frequently performed, and further there are many opportunities for performing the printing or another operation. In a use mode in which the storage medium is included in the digital camera, particularly a user's operation property can be enhanced.

The present invention is not limited to the aforementioned embodiment, and various modifications are possible in a scope claimed in the following claims.

0904050-22E34850